

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1 1. (Currently Amended) A method for processing incoming print jobs,
- 2 comprising:
- 3 examining job description attributes of a print job being received on a print channel
- 4 and identifying the attribute of the print job;
- 5 identifying an attribute of the print channel associated with the incoming print job;
- 6 and
- 7 processing the incoming print job based upon the job description attribute of the
- 8 incoming print job and the identification of the attribute of the print channel receiving the
- 9 print job;
- 10 wherein the print channel attribute is MUST PRINT for print channels that provide
- 11 bi-directional communication with a host and the print channel attribute is MAY SPOOL for
- 12 Web Pull, Web Push, IPP, FTP, direct print ports, LPD, NetBIOS, NetWare, and Parallel
- 13 type print control modules.

1 2. (Original) The method of claim 1 wherein the processing further
2 comprises:
3 determining whether the job description attributes and the print channel attributes
4 dictate an output path;
5 analyzing a state for a dictated output path when the job description attributes and the
6 print channel attributes dictate an output path; and
7 routing the incoming print job to the dictated path when the state of the dictated path
8 is free.

1 3. (Original) The method of claim 2 further comprising signaling a stop flow
2 command to halt the incoming print job when the state of the dictated path is busy.

1 4. (Original) The method of claim 3 further comprising restarting the
2 incoming print job when the dictated path becomes available.

1 5. (Original) The method of claim 2 further comprising:
2 evaluating a setting for a user output selection when the job description attributes and
3 the print channel attributes do not dictate an output path; and
4 processing the incoming print job based upon the setting for the user output selection.

1 6. (Original) The method of claim 5 further comprising:
2 printing the incoming print job when the incoming print job is not required to be
3 spooled because of the job description attributes or the print channel attributes and the setting
4 of the user output selection is PRINT ALL;
5 spooling the incoming print job when the incoming print job is not required to be
6 printed because of the job description attributes or the print channel attributes and the setting
7 of the user output selection is SPOOL ALL;
8 printing the incoming print job when the printer is available, the incoming print job is
9 not required to be printed because of the job description attributes or the print channel
10 attributes and the setting of the user output selection is SPOOL WHEN BUSY; and
11 spooling the incoming print job when the printer is busy, the incoming print job is not
12 required to be printed because of the job description attributes or the print channel attributes
13 and the setting of the user output selection is SPOOL WHEN BUSY.

1 7. (Canceled)

1 8. (Canceled)

1 9. (Currently Amended) The method of claim [[8]] 1 wherein the print channel
2 attribute is MUST PRINT for a IPDS port, Coax, Twinax, AppleTalk, Despooler and Internal
3 Print type print control modules.

1 10. (Canceled)

1 11. (Currently Amended) The method of claim [[8]] 1 wherein the determining
2 job description attributes of an incoming print job further comprises scanning a data stream
3 for the incoming print job.

1 12. (Canceled)

1 13. (Previously Presented) The method of claim 1, wherein a PDF file
2 comprises a MUST SPOOL job description attribute.

1 14. (Original) The method of claim 13 wherein the PDF file is spooled to
2 allow the PDF file to be converted to PostScript before printing.

1 15. (Previously Presented) The method of claim 1, wherein an IPDS file
2 comprises a MUST PRINT job description attribute.

1 16. (Currently Amended) A multiplexer for processing incoming print jobs,
2 comprising:
3 a multiplexer interface for examining job description attributes of a print job being
4 received on a print channel and identifying the attribute of the print job and identifying an
5 attribute of the print channel associated with the incoming print job; and
6 a multiplexer processor component, interfaced with the multiplexer interface, for
7 processing the incoming print job based upon the job description attribute of the incoming
8 print job and the identification of the attribute of the print channel receiving the print job;
9 wherein the print channel attribute is MUST PRINT for print channels that provide
10 bi-directional communication with a host and the print channel attribute is MAY SPOOL for
11 Web Pull, Web Push, IPP, FTP, direct print ports, LPD, NetBIOS, NetWare, and Parallel
12 type print control modules.

1 17. (Original) The multiplexer of claim 16 wherein the multiplexer processor
2 component determines whether the job description attributes and the print channel attributes
3 dictate an output path, analyzes a state for a dictated output path when the job description
4 attributes and the print channel attributes dictate an output path and routes the incoming print
5 job to the dictated path when the state of the dictated path is free.

1 18. (Original) The multiplexer of claim 17 wherein the multiplexer processor
2 component signals a stop flow command to halt the incoming print job when the state of the
3 dictated path is busy.

1 19. (Original) The multiplexer of claim 18 wherein the multiplexer processor
2 component restarts the incoming print job when the dictated path becomes available.

1 20. (Original) The multiplexer of claim 17 further comprises a multiplexer
2 output selector for receiving a user selection input to control spooling of jobs that are not
3 required to be sent to a spooler or a print engine, wherein the multiplexer processor
4 component evaluates a setting for a user output selection when the job description attributes
5 and the print channel attributes do not dictate an output path and routes the incoming print
6 job based upon the setting for the user output selection.

1 21. (Original) The multiplexer of claim 20 wherein the multiplexer processor
2 component prints the incoming print job when the incoming print job is not required to be
3 spooled because of the job description attributes or the print channel attributes and the setting
4 of the user output selection is PRINT ALL, spools the incoming print job when the incoming
5 print job is not required to be printed because of the job description attributes or the print
6 channel attributes and the setting of the user output selection is SPOOL ALL, prints the
7 incoming print job when the printer is available, the incoming print job is not required to be
8 printed because of the job description attributes or the print channel attributes and the setting
9 of the user output selection is SPOOL WHEN BUSY and spools the incoming print job when
10 the printer is busy, the incoming print job is not required to be printed because of the job
11 description attributes or the print channel attributes and the setting of the user output
12 selection is SPOOL WHEN BUSY.

1 22. (Canceled)

1 23. (Canceled)

1 24. (Currently Amended) The multiplexer of claim [[23]] 16 wherein the print
2 channel attribute is MUST PRINT for a IPDS port, Coax, Twinax, AppleTalk, Despooler and
3 Internal Print type print control modules.

1 25. (Canceled)

1 26. (Currently Amended) The multiplexer of claim [[23]] 16 wherein the print
2 channel scans a data stream for the incoming print job to determine the job description
3 attributes of the incoming print job.

1 27. (Canceled)

1 28. (Previously Presented) The multiplexer of claim 16, wherein a PDF file
2 comprises a MUST SPOOL job description attribute.

1 29. (Original) The multiplexer of claim 28 wherein the multiplexer processor
2 component spools the PDF file to allow the PDF file to be converted to PostScript before
3 printing.

1 30. (Previously Presented) The multiplexer of claim 16, wherein an IPDS
2 file comprises a MUST PRINT job description attribute.

1 31. (Currently Amended) A print system, comprising:
2 a print engine for receiving a data stream for an incoming print job and generates print
3 media based upon the data stream;
4 a spooler storing incoming print jobs until sent to the print engine; and
5 a system controller, coupled to the print engine and the spooler, for controlling the print
6 engine, the spooler and the processing of incoming print jobs, the system controller including a
7 multiplexer for managing the incoming print jobs, the multiplexer further comprising:
8 a multiplexer interface for examining job description attributes of a print job
9 being received on a print channel and identifying the attribute of the print job and identifying
10 an attribute of the print channel associated with the incoming print job; and
11 a multiplexer processor component, interfaced with the multiplexer interface,
12 for processing the incoming print job based upon the job description attribute of the incoming
13 print job and the identification of the attribute of the print channel receiving the print job;
14 wherein the print channel attribute is MUST PRINT for print channels that
15 provide bi-directional communication with a host and the print channel attribute is MAY
16 SPOOL for Web Pull, Web Push, IPP, FTP, direct print ports, LPD, NetBIOS, NetWare, and
17 Parallel type print control modules.

1 32. (Original) The print system of claim 31 wherein the multiplexer processor
2 component determines whether the job description attributes and the print channel attributes
3 dictate an output path, analyzes a state for a dictated output path when the job description
4 attributes and the print channel attributes dictate an output path and routes the incoming print job
5 to the dictated path when the state of the dictated path is free.

1 33. (Original) The print system of claim 32 wherein the multiplexer processor
2 component signals a stop flow command to halt the incoming print job when the state of the
3 dictated path is busy.

1 34. (Original) The print system of claim 33 wherein the multiplexer processor
2 component restarts the incoming print job when the dictated path becomes available.

1 35. (Original) The print system of claim 32 further comprises a multiplexer
2 output selector for receiving a user selection input to control spooling of jobs that are not
3 required to be sent to a spooler or a print engine, wherein the multiplexer processor
4 component evaluates a setting for a user output selection when the job description attributes
5 and the print channel attributes do not dictate an output path and routes the incoming print
6 job based upon the setting for the user output selection.

1 36. (Original) The print system of claim 35 wherein the multiplexer processor
2 component prints the incoming print job when the incoming print job is not required to be
3 spooled because of the job description attributes or the print channel attributes and the setting
4 of the user output selection is PRINT ALL, spools the incoming print job when the incoming
5 print job is not required to be printed because of the job description attributes or the print
6 channel attributes and the setting of the user output selection is SPOOL ALL, prints the
7 incoming print job when the printer is available, the incoming print job is not required to be
8 printed because of the job description attributes or the print channel attributes and the setting
9 of the user output selection is SPOOL WHEN BUSY and spools the incoming print job when
10 the printer is busy, the incoming print job is not required to be printed because of the job
11 description attributes or the print channel attributes and the setting of the user output
12 selection is SPOOL WHEN BUSY.

1 37. (Canceled)

1 38. (Canceled)

1 39. (Currently Amended) The print system of claim [[38]] 31 wherein the print
2 channel attribute is MUST PRINT for a IPDS port, Coax, Twinax, AppleTalk, Despooler and
3 Internal Print type print control modules.

1 40. (Canceled)

1 41. (Currently Amended) The print system of claim [[38]] 31 wherein the print
2 channel scans a data stream for the incoming print job to determine the job description
3 attributes of the incoming print job.

1 42. (Canceled)

1 43. (Previously Presented) The print system of claim 31, wherein a PDF
2 file comprises a MUST SPOOL job description attribute.

1 44. (Original) The print system of claim 43 wherein the multiplexer processor
2 component spools the PDF file to allow the PDF file to be converted to PostScript before
3 printing.

1 45. (Previously Presented) The print system of claim 31, wherein an IPDS
2 file comprises a MUST PRINT job description attribute.

1 46-50. (Canceled)